

AUTO WASH

AUTO WASH AND WAX

PRODUCT CODE: 110

DESCRIPTION AND PRODUCT BENEFITS:

As a one-step wash and wax, AUTO WASH penetrates and removes stubborn dirt, while producing a lustrous sheen. The extensive capabilities of AUTO WASH offers a straightforward, environmentally friendly, effective vehicle wash method. Drying and wax agents enhance ability of water beading; for a simple dry and provisional wax. Certified biodegradable according to OECD-301 testing. Designed for use in both automatic and manual friction vehicle washes.

DIRECTIONS OF USE AND APPLICATION:

1. Dilute 8 mL of AUTO WASH per 1 L of water. (1:128). 2. Wet vehicle surface and apply AUTO WASH solution. 3. Agitate solution. For manual friction application: wash mitt or vehicle brush. For automatic friction application: use brush tunnel wash, or cloth tunnel wash. 4. Rinse vehicle thoroughly, from the top down. 5. Remove excess water. Tips: Do not wash vehicle in direct sunlight. Hydro System proportioner metering tip (25 psi & 20°C): Large thread, tan / medium brown, size 0.035 tip.

PRECAUTIONS:

Do not mix with other chemicals. Keep from freezing.

HEALTH & SAFETY INFORMATION:

For further information on the safe handling, storage and precautions for use of this product, consult the Safety Data Sheet. Keep out of reach of children.

DISCLAIMER:

As the actual conditions of use are out of our control no liability is accepted for any loss or damage caused directly or indirectly through the use of our products. Intending users should satisfy themselves, by carrying out appropriate tests, as to the suitability of this product for any particular purpose.



TYPICAL DATA:

APPEARANCE: Purple viscous liquid.

SPECIFIC GRAVITY: ~ 1.02 g/ml

ODOUR: Fruity.

UNDILUTED PH: ~ 9.0 ± 0.5

DILUTED 1:128 PH: ~ 7.8

SOLUBILITY: Completely water soluble.

VISCOSITY: 600 ± 10% cps @ 20°C

AVAILABLE SIZES:



- A11012 - **JUG** - 3.78 L / 1 US GAL
- A11014 - **CUBE** - 18.9 L / 5 US GAL
- A11016 - **KEG** - 56.8 L / 15 US GAL
- A11018 - **DRUM** - 208.2 L / 55 US GAL
- BA110 - **WORKPLACE LABEL**

